

## magROCK Features

- **High sensitivity** yet Stable (low noise) instrument
- **Low frequency** for deeper penetration of rock samples
- **User friendly** Menu System for non-geophysicist
- **Reversible display** for 'ease of reading' when upside-down
- **Digital and analogue** display for easy reading of results
- **Ruggedised** with ergonomically designed case
- **Large Memory** stores 30 sets of 128 reading, total 3,840 individual reading
- Data transfer by **USB cable** (waterproof connector)
- Reads in SI and CGS Units



The **magROCK** is a new instrument incorporating the latest in display technology and sound physical principles that enable improved sensitivity and accuracy. By utilising a **low 750 Hz** measurement frequency and two ferrite cored coils, the **magROCK** has overcome problems often encountered by high frequency, smaller single coil devices such as:

- Erroneous readings caused by the simultaneous measurement of sample conductivity and susceptibility.
- Lack of penetration of the measurement beyond the surface of the sample.

The **magROCK** has been designed to be easy to use by non technical people. Readings are represented as both an analogue bar chart and a digital readout. Also, the menu is highly intuitive and the real-time scan mode enables readings to be optimised. Alternatively, there is a step mode for recording fixed readings on the display. Both modes can be saved to the extensive memory at the push of one button and the storage location is conveniently noted on the display.

## Other Features

- Reads in both SI and CGS units
- Can be operated remotely using a PC and a USB cable
- Easy to use with one hand
- Scanning mode with audio to identify peak value
- Rugged and water-resistant (EP65 case)
- Long battery life
- Fast zeroing (approx. 7 seconds)

## Accessories

- Leather belt pouch
- USB download cable
- Padded Pelican case
- Software
- Instruction Manual



## Technical Specifications

### Electrical

Sensitivity	1 x 10 <sup>-5</sup> SI Units
Range	1 x 10 <sup>-5</sup> to 10 SI Units
Sensor Oscillating Frequency	750 Hz.
Operating Mode	Single reading or Continuous

### Mechanical

Display Size	5.8 x 3.0 cm
Power Source	3 x AA alkaline batteries
Battery Life	40 hours (using alkaline batteries)
Operating Temp. Range	0 to +50 deg C.
Storage Temp. Range	-40 to 60 deg C.
Dimensions	16 x 8 x 4 cm
Weight of Instrument	365 gm with battery

Developed and Produced in collaboration with Geo Equipment Repairs & Services Pty. Ltd. – Sydney, Australia.

## Further Information

For further information regarding this product, either technical or sales, please contact:



Unit 1, 43 Stanley Street, Peakhurst. N.S.W. 2210. Australia  
**Phone** +61 (0) 2 9584 7555 **Fax** +61 (0) 2 9584 7599  
**e-mail** info@alpha-geo.com **website** www.alpha-geo.com

Your Distributor: